



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 1/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

## Safety Data Sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **BRAKE FLUID DOT3 EX 9203001, 9203002**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **BRAKE FLUID DOT 3 (for B2C)**

Identified Uses	Industrial	Professional	Consumer
Functional Fluids	✓	✓	✓

#### 1.3. Details of the supplier of the safety data sheet

Name **FTE automotive GmbH**  
Full address **Postfach 11 80 / D-96104 Ebern  
Andreas-Humann-Str. 2,  
D-96106 Ebern**  
District and Country  
Phone +49-9531-81-0  
Fax +49-9531-81-3377

e-mail address of the competent person responsible for the Safety Data Sheet **pts.ebern.mailbox@valeo.com**

**1.4. Emergency telephone number** **+49-9531-81-0 (business hours)**  
For urgent inquiries refer to

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety data sheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4	H302	Harmful if swallowed.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.

#### 2.2. Label elements

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

**H302** Harmful if swallowed.  
**H373** May cause damage to organs through prolonged or repeated exposure.  
**H318** Causes serious eye damage.

Precautionary statements:

**P101** If medical advice is needed, have product container or label at hand.  
**P102** Keep out of reach of children.  
**P264** Wash hands thoroughly after handling.  
**P280** Wear eye protection / face protection.  
**P301+P312** IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.  
**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P501** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Contains:** DIETHYLENE GLYCOL  
ETHANOL, 2-BUTOXY-, manuf. of, by-products from

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients**

**3.1. Substances**

Information not relevant

**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
----------------	-------------	--------------------------------



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 3/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

**ETHANOL, 2-BUTOXY-, manuf. of, by-products from**

CAS 161907-77-3                       $65 \leq x < 70$                       Eye Dam. 1 H318

EC 310-287-7

INDEX -

Reg. no. 01-2119475115-41-xxxx

**DIETHYLENE GLYCOL**

CAS 111-46-6                       $30 \leq x < 35$                       Acute Tox. 4 H302, STOT RE 2 H373

EC 203-872-2

INDEX 603-140-00-6

Reg. no. 01-2119457857-21-xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

### 5.2. Special hazards arising from the substance or mixture

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 4/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

**5.3. Advice for firefighters**

**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage**

**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available



**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

**SECTION 8. Exposure controls/personal protection**

**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 4. 11.2016) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Graensev aerder per stoffer og materialer
GBR	United Kingdom	EH40/2005 Workplace exposure limits
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18

**ETHANOL, 2-BUTOXY-, manuf. of, by-products from**

Predicted no-effect concentration - PNEC

Normal value in freshwater	4,5	mg/l
Normal value in marine water	0,31	mg/l
Normal value for fresh water sediment	6,6	mg/kg
Normal value for marine water sediment	0,66	mg/kg
Normal value for water, intermittent release	24,9	mg/l
Normal value of STP microorganisms	500	mg/l
Normal value for the terrestrial compartment	1,32	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				2,5 mg/kg bw/d				
Inhalation				117 mg/m3				195 mg/m3
Skin				25 mg/kg bw/d				50 mg/kg bw/d

**DIETHYLENE GLYCOL**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	44	10	176	40	
MAK	DEU	44	10	176	40	
TLV	DNK	11	2,5			
WEL	GBR	101	23			
MAK	SWE	45	10	90	20	SKIN

Predicted no-effect concentration - PNEC

Normal value in freshwater	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	20,9	mg/kg
Normal value for marine water sediment	2,09	mg/kg
Normal value for water, intermittent release	10	mg/l



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 6/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

Normal value of STP microorganisms	199,5	mg/l					
Normal value for the terrestrial compartment	1,53	mg/kg					
<b>Health - Derived no-effect level - DNEL / DMEL</b>							
	Effects on consumers		Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute systemic	Chronic local	Chronic systemic
Inhalation			12 mg/m <sup>3</sup>	12 mg/m <sup>3</sup>		60 mg/m <sup>3</sup>	60 mg/m <sup>3</sup>
Skin			VND	53 mg/kg/d		VND	53 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent an accidental absorption.

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	colourless to amber
Odour	characteristic
Odour threshold	Not available
pH	7 - 11,5
Melting point/ freezing point	Not available
Initial boiling point	> 235 °C
Boiling range	Not available
Flash point	> 100 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,000 - 1,100
Solubility	soluble
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC (Directive 2010/75/EC):	0
VOC (volatile carbon):	0

**SECTION 10. Stability and reactivity**



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 8/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

**10.1. Reactivity**

The product may react exothermally on contact with strong oxidising or reducing agents, strong acids or bases.

**10.2. Chemical stability**

Excessively high temperatures can cause thermal decomposition.

Hygroscopic.

**10.3. Possibility of hazardous reactions**

See paragraph 10.1.

**10.4. Conditions to avoid**

Avoid overheating.

**10.5. Incompatible materials**

Oxidising or reducing agents. Strong acids or bases.

ETHANOL, 2-BUTOXY-, manuf. of, by-products from

Avoid contact with: water.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**SECTION 11. Toxicological information**

**11.1. Information on toxicological effects**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure





FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 9/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:  
Not classified (no significant component)  
LD50 (Oral) of the mixture:  
1538,46 mg/kg  
LD50 (Dermal) of the mixture:  
Not classified (no significant component)

ETHANOL, 2-BUTOXY-, manuf. of, by-products from

LD50 (Oral) 2630 mg/kg bw

LD50 (Dermal) 3540 mg/kg bw

DIETHYLENE GLYCOL

LD50 (Oral) 19600 mg/kg

LD50 (Dermal) 13300 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information****12.1. Toxicity**ETHANOL, 2-BUTOXY-, manuf. of, by-  
products from

LC50 - for Fish	> 1800 mg/l/96h
EC50 - for Crustacea	> 3200 mg/l/48h
EC50 - for Algae / Aquatic Plants	391 mg/l/72h
EC10 for Algae / Aquatic Plants	188 mg/l/72h

DIETHYLENE GLYCOL

LC50 - for Fish	> 100 mg/l
Chronic NOEC for Fish	> 100 mg/l

**12.2. Persistence and degradability**ETHANOL, 2-BUTOXY-, manuf. of, by-  
products from  
Rapidly degradable

DIETHYLENE GLYCOL

Rapidly degradable

**12.3. Bioaccumulative potential**

ETHANOL, 2-BUTOXY-, manuf. of, by-



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 11/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

products from

Partition coefficient: n-octanol/water 0,44

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 12/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 13/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has been performed for the following contained substances

ETHANOL, 2-BUTOXY-, manuf. of, by-products from

DIETHYLENE GLYCOL

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>H302</b>	Harmful if swallowed.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%



FTE AUTOMOTIVE GmbH

Revision nr. 1

Dated 13/03/2018

First compilation

Printed on 14/10/2019

Page n. 14/14

**BRAKE FLUID DOT3 EX**  
(9203001, 9203002)

**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

msds for B2C.

**Changes to previous review:**

The following sections were modified:

03.